

HP - Spray Gun KSP 1200 valve actuated	Z 3-1 e
	18.07.2013

- HP - Gun complete with spray tube 750 mm, handle and nozzle holder for insert nozzles (without hose connector and nozzle)

Part No. 7009209



Additional equipment

- Shoulder support Part No. 7009215
- Initiator for remote control with 2 m cable and plug Part No. 7017928
- Half shell handle Part No. 7009921
- Hose connection adapter M 22x1.5 Part No. 7009212
- Hose connection adapter M 24x1.5 Part No. 7009213
- Hose connection adapter G 1/2" Part No. 7012416



Technical data

Max. working pressure:	1200 bar
Max. capacity:	40 l/min
Connection:	M 26x1.5 female (with pressure screw M 26x1.5 and pressure ring M 14x1.5 LH)
Total length:	1000 mm
Weight:	approx. 3.4 kg
Temperature:	max. 50°C
Usable nozzle inserts:	Insert nozzles Form A, B and C (see page Z 41-1 e + Z 41-2 e) Orbital nozzle KOD 1500/1000 (see page Z 40-1/2/3/4 e) Rotating nozzle PRD 2000 (see page Z 15-1 e)

Applications

For manual surface cleaning of all type of forms and materials with nozzle.



For hand-held operation of a spray gun the nozzle diameter must be selected to ensure that the reaction force in the longitudinal axis when used at the max. operating pressure does not exceed 250 N. If the reaction force is in excess of 150 N the gun must be equipped with a support, in compliance with the European Norm EN 1829.