

HP - Spray Gun KSP 500

Z 1-1e

valve actuated

01.12.2011

- HP - Gun complete with spray tube
500 mm or 1000 mm and handle
(without hose connector and nozzle)
- KSP 500 with 500 mm spray tube Part no. 7002580
- KSP 500 with 1000 mm spray tube Part no. 7002581
- Hose connector G 1/2" Part no. 5040033
- Hose connector M 22x1.5 DKL Part no. 1051093
- Sleeve G 1/4" for screwed nozzles Part no. 1050088



Technical Data

Max. working pressure:	600 bar
Max. capacity:	80 l/min
Connection:	G 1/2" female
Nozzle connection:	G 1/4" male
Total length:	650 mm or 1150 mm - depending on actual model
Weight:	approx. 3 - 4 kg - depending on actual model
Temperature:	max. 150°C
Usable nozzle inserts:	Screwed nozzles G 1/4" (see page Z 42-1 e) only with sleeve 1050088 Orbital nozzle KOD 500 (see page Z 40-1/2/3/4 e)

Applications

For manual surface cleaning of all types of forms and materials with nozzle.



For hand-held operation of a spray gun the nozzle diameter must be selected to ensure that the reaction force in the longitudinal axis when used at the max. operating pressure does not exceed 250 N. If the reaction force is in excess of 150 N the gun must be equipped with a support, in compliance with the European Norm EN 1829.